


Technical sheet :

MTA 5519 S3

 MTA 5519 S3

Capacities		Metric	Imperial
Max. capacity	Q	2495 kg	5501 lbs
Max. lifting height	h3	5.8 m	19 ft
Max. Reach	l4	3.35 m	11 ft
Weight and dimensions			
Overall length to carriage	l11	3.76 m	12 ft 4 in
Overall length (with forks)	l1	3.76 m	12 ft 4 in
Overall width	b1	1.8 m	5 ft 11 in
Overall height	h17	1.93 m	6 ft 4 in
Wheelbase	y	2.29 m	7 ft 6 in
Ground clearance	m4	266 mm	10.472 in
Overall cab width	b4	711 mm	27.992 in
Tilt-up angle	a4	12 °	12 °
Tilt-down angle	a5	100 °	100 °
Outer turning radius	Wa3	3.35 m	11 ft
Unladen weight (with forks)		4400 kg	9700 lbs
Standard tyres		12 x 16.5	12 x 16.5
Performances			
Lifting		8 s	8 s
Lowering		5 s	5 s
Extension		7 s	7 s
Retraction		6 s	6 s
Scoop		4 s	4 s
Crowd		4 s	4 s
Dump		4 s	4 s
Engine			
Engine brand		Yanmar	Yanmar
Engine norm		Tier IV Final	Tier IV Final
Engine model		4TNV98	4TNV98
Number of cylinders / Capacity of cylinders		4 - 3.32 cm ³	4 - 0.2 in ³
Power (kW)		50.7 kW	50.7 kW
Max. torque / Engine rotation		235 @ 235 tr/min	235 @ 235 tr/min
Transmission			
Transmission type		Hydrostatic	Hydrostatic
Number of gears (forward / reverse)		2 / 2	2 / 2
Parking brake		Sahr	Sahr
Service brake		Wet disc brakes	Wet disc brakes
Axle Manufacturer		Dana	Dana
Hydraulics			
Hydraulic pump type		Gear Pump	Gear Pump
Hydraulic flow / Pressure		83 l/min / 231 Bar	83 l/min / 16 PSI
Tank capacities			
Engine oil		9 l	1.98 gal
Hydraulic oil		68 l	14.96 gal
Fuel tank		64 l	14.08 gal
Miscellaneous			
Steering wheels (front / rear)		2 / 2	2 / 2
Drive wheels (front / rear)		2 / 2	2 / 2
Safety cabin homologation		ROPS/FOPS	ROPS/FOPS
Controls		Single Joystick FNR	Single Joystick FNR

Dimensional drawing





Siège Social

430 rue de l'Aubinière - 44150 Ancenis Cedex - France

Tel: +33(0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

www.manitou.com



This brochure describes versions and configuration options for Manitou products which may be fitted with different equipment. The equipment described in this brochure may be standard, optional or not available depending on version. Manitou reserves the right to change the specifications shown and described at any time and without prior warning. The manufacturer is not liable for the specifications given. For more information, contact your Manitou dealer. Non-contractual document. Product descriptions may differ from actual products. List of specifications is not comprehensive. The logos and visual identity of the company are the property of Manitou and may not be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are provided for information only.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,547,824 euros - 857 802 508
RCS Nantes